

With or without
buzzerr

Multicolour
(3 or 7 colours)

MC 55 -
now also available
with UL approval

IP 65 / IP 69k



With the two LED installation beacons, MC55 and MC35, WERMA offers a compact signal device with up to seven colours in one beacon: red, yellow, green, white, blue, violet and turquoise. Alternatively a tricolour version is available, which combines the most common colour combination of red, yellow and green in one signal device.

LED Installation Beacon MC55 and MC35

240 LED Multicolour Beacon MC55



Technical Specifications

Dimensions (Ø x H)	55 mm x 46 mm (Protrusion from panel)
Housing	PC/ABS-Blend, black PC, black (UL approval)
Lens	PC, transparent
Fixing	Installation mounting M30
Colour options	Red, yellow, green, white, blue, violet, turquoise (RGB) Red, yellow, green (RGY)
Light effect	Permanent Permanent and Blinking light (1 Hz) (240 110 50 / 240 130 50)
Tone types and frequency	Pulse tone, 3400 Hz
Life duration light	Up to 50,000 h
Life duration buzzer	Up to 5,000 h
Working temperature min./max.	-20°C / +50°C

With buzzer

Protection rating	IP 65			
Sound output	85 dB (A)			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 240 55	240 230 55
Multicolour (RGB)	10-30 V DC	80 mA	240 140 50	240 130 50

UL approval with buzzer

Protection rating	IP 69k			
	Voltage	Current consumption	Plug M12	
Tricolor (RGY)	24 V DC	65 mA	240 440 55	
Multicolour (RGB)	10-30 V DC	130 mA	240 340 50	

Without buzzer

Protection rating	IP 65			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 220 55	240 210 55
Multicolour (RGB)	10-30 V DC	60 mA	240 120 50	240 110 50

UL approval without buzzer

Protection rating	IP 69k			
	Voltage	Current consumption	Plug M12	
Tricolor (RGY)	24 V DC	40 mA	240 420 55	
Multicolour (RGB)	10-30 V DC	120 mA	240 320 50	



NEW

241 LED Multicolour Beacon MC35

Technical Specifications

Dimensions (Ø x H)	35 mm x 64 mm (Protrusion from panel)
Housing	PC, black
Lens	PC, transparent
Fixing	Installation mounting M22
Colour options	Red, yellow, green, white, blue, violet, turquoise (RGB) Red, yellow, green (RGY)
Light effect	Permanent light
Tone types and frequency	Continuous tone, 3600 Hz
Life duration light	Up to 50,000 h
Life duration buzzer	Up to 5,000 h
Working temperature min./max.	-20°C / +50°C

UL approval with buzzer

Protection rating	IP 69k		
Sound output	80 dB (A)		
	Voltage	Current consumption	M12
Tricolor (RGY)	24 V DC	45 mA	241 440 55
Multicolour (RGB)	10-30 V DC	45 mA	241 340 50

UL approval without buzzer

Protection rating	IP 69k		
	Voltage	Current consumption	M12
Tricolor (RGY)	24 V DC	20 mA	241 420 55
Multicolour (RGB)	10-30 V DC	30 mA	241 320 50



WERMA Signaltechnik GmbH + Co. KG

Dürbheimer Str. 15
D- 78604 Rietheim- Weilheim
Phone +49 74 24 95 57- 0
Fax +49 74 24 95 57- 44
www.werma.com | info@werma.com

WERMA Signaltechnik

Niederlassung Neuhausen am Rhf.
Rheingoldstrasse 50
8212 Neuhausen am Rheinfall
Switzerland
Phone +41 52 674 00 60
Fax +41 52 674 00 66
www.werma.ch | info@werma.ch

WERMA Italia S.r.l.

Via dell'Artigianato 42
29122 Piacenza
Italia
Phone +39 523 044 544
www.werma.it | info@werma.it

WERMA SARL

56, Rue Colière
69780 Mions
France
Phone +33 472 22 37 37
www.werma.fr | info@werma.fr

WERMA BENELUX

Poortakkerstraat 41C
9051 Sint-Denijs-Westrem
Belgium
Phone +32 9 220 3111
www.wermabenelux.com | info@wermabenelux.com

WERMA (UK) Ltd.

11 Regent Park
37 Booth Drive
Park Farm Industrial Estate
Wellingborough NN8 6GR
Great Britain
Phone +44 1536 48 69 30
Fax +44 1536 51 48 10
www.werma.co.uk | uksales@werma.co.uk

WERMA USA Inc.

1266 Oakbrook Drive, Suite A
Norcross, GA 30093 USA
Phone +1 470 361 0600
www.werma.com | us-info@werma.com

WERMA (Shanghai) Co., Ltd.

Building 8, No. 85, Mingnan Road, Songjiang, Shanghai, P. R. C
201613
China
Phone +86 215774- 00 22
Fax +86 215774- 66 01
www.werma.com.cn | info@werma.com.cn